

# PM600

Coolcor  
Long Life HD Coolant  
100% Concentrate

## Organic Acid Technology Universal Engine Coolant

### Product Information

PM600 Coolcor Long Life HD Coolant is a long-life, ethylene glycol-based anti-boil, anti-freeze coolant and an organic-acid-based rust and electrolysis inhibitor, developed to meet engine manufacturers' requirements and deliver excellent performance in low and high temperature operation, providing the required protection. Long-life hybrid technology has a decisive advantage in its robustness against conventional and Organic Acid Technology (OAT) engine coolants and is fully compatible with both. PM600 Coolcor Long Life HD contains 90% high-grade mono-ethylene glycol and premium OAT inhibitors.

PM600 Coolcor Long Life HD meets the phosphate-free requirements of European manufacturers and the silicate-free requirements of Japanese manufacturers. It is recommended for use in all passenger cars, 4WDs, and light- and heavy-duty diesel applications, including safeguarding aluminium in high-temperature zones.

**Service Life:** PM600 Coolcor Long Life HD has a service life of 10 years/1,000,000 km for Automotive and Heavy-Duty Engines. PM600 Coolcor Long Life HD does not require an initial charge of supplemental coolant additives (SCAs) for initial fill in heavy-duty diesel applications, as the product is formulated to protect diesel engine wet sleeve liners.

**Dilution Rate:** PM600 Coolcor Long Life HD, in the absence of manufacturers' recommendations, use 33%-50% PM600 Coolcor and the balance demineralised water.

\*\*PM 600 Coolcor Long Life HD is compatible with coolant filtration when administered at 50% concentration with deionised water.

### Benefits

- **Extended Life Protection & Performance**
- **Low Ambient Temperature Protection**
- **Protects Against Corrosion**
- **Phosphate and Amine Free**
- **Water Pump Lubrication**
- **Compatibility With Seals & Hoses**
- **Meets or Exceeds OEM Approvals**
- **Universal Use**
- **Glycol Fortified**

### PM600 Coolcor Long Life HD Coolant Meets OEM Requirements Where Called For

ATM D-3306, D-4895, D6210	Land Rover
Caterpillar EC1	Mack Trucks
Cummins 14603	MAN 324
Daimler Chrysler MS7170, MS9769	Mercedes-Benz DBL 325
Detroit Diesel 7SE 298	MTU MTL 5048
Ford ESE-M97B44A, ESE-M97B18C, WSS-M97B51-A1	New Holland WSN-M97B18-D
Freightliner 48-2288D	PACCAR
GM1825M, 1899M, GM Heavy Truck	Perkins
Hyundai SAE J1034, J1941	Peterbilt 8502.002
JIS K2234	Saab-Scania 6901
Kenworth RO26-170-97	TMC RP329
	US Federal A-A-870-A
	Volvo Heavy Truck
	White Star

### PM600 Coolcor

**Provides the Required Protection**

### Why PM Lubrication?

- ❖ **Premium Quality**
- ❖ **XPR Protection Reserve**
- ❖ **Cost Effective Lubrication**
- ❖ **On-Site Monitoring will maximise equipment life**
- ❖ **Knife Edge Filtration**
- ❖ **Our Predictive & Preventative Maintenance Programme is GUARANTEED to save 15% of your total operating costs**

Available in 20L, 5L Containers

Issued 6/02/2026



AUSTRALIAN OWNED

PM Lubrication  
4/105 Archibald St, Paget  
Queensland 4740 Australia

Tel: 07 4998 5851 Mob: 0419 771 825

[www.pmlubrication.com.au](http://www.pmlubrication.com.au) [hello@pmlubrication.com.au](mailto:hello@pmlubrication.com.au)

